



Model 850-4-75 Shown

- 4" FPT fill (to 4" MPT tank opening)
- 1/2" return. 7 1/2 GAL capacity.

Model 880-2-50 Shown

- 2" FPT center opening only.
- 5 GAL capacity.
- internal optional screen.

Lockable Lid, domed.

TYPICAL APPLICATIONS

MATERIALS:

PAN AND LID ARE OF SPUN COLD ROLLED STEEL.

FILL AND DRAIN OPENINGS, STEEL SCH 40 MINIMUM.

FINISH IS EPOXY POWDERCOATED, INTERIOR AND EXTERIOR (ALTERNATE STAINLESS STEEL).

CAUTION

FLAMMABLE OR COMBUSTIBLE LIQUIDS/VAPORS MAY BE PRESENT. KEEP AWAY SPARKS, FLAME, IGNITION SOURCES. EXTINGUISH SMOKING MATERIALS. FOR USE ONLY ON PROPERLY VENTED ABOVEGROUND STORAGE TANKS. KEEP LID CLOSED AND OPENINGS SECURELY PLUGGED EXCEPT DURING ACTUAL TANK FILLING.

This drawing and design are proprietary to BAKER INDUSTRIES NORTHWEST, and may not be copied or duplicated in whole or in part without the written permission of BAKER INDUSTRIES NW.

#800 TANK TOP SPILL CONTAINMENT

BAKER INDUSTRIES NORTHWEST

12428 Highway 99 South, Unit 56
Everett, Washington 98204-5502

Tel: (425) 212-3169 • FAX: (425) 353-6788 • e-mail: larry@bakerindnw.com
www.bakerindustriestnorthwest.com

	REV		DRAWN	CHECKED	DATE
	REV		LRG	RBW	09-19-97
	REV		SLG	LRG	03-05-06
	REV				

